

KAWEFLEX® 3420 SK-C-SI-180

温度达+180°C(屏蔽型)

芯线根数及 导体截面积 n x mm²	电缆近 似外径 mm(ca.)	电缆消 耗铜量 kg/km	电缆近 似重量 kg/km(ca.)	芯线根数及 导体截面积 n x mm²	电缆近 似外径 mm(ca.)	电缆消 耗铜量 kg/km	电缆近 似重量 kg/km(ca.)
3 G 0,5	6,0	28,0	79,0	3 G 1,5	8,5	62,0	139,0
4 G 0,5	6,6	33,0	93,0	4 G 1,5	9,4	80,0	156,0
5 G 0,5	7,2	40,0	107,0	5 G 1,5	10,3	95,0	198,0
7 G 0,5	8,4	56,0	132,0	7 G 1,5	12,3	145,0	254,0
12 G 0,5	10,4	81,0	190,0	12 G 1,5	15,4	228	416,0
18 G 0,5	12,2	120,0	245,0	18 G 1,5	18,2	340,0	564,0
25 G 0,5	15,0	181,0	281,0	25 G 1,5	22,4	490,0	811,0
34 G 0,5	17,0	235,0	449,0				
42 G 0,5	19,1	275,0	554,0				
				4 G 2,5	10,5	119,0	190,0
3 G 0,75	6,5	36,0	96,0	5 G 2,5	11,6	145,5	235,0
4 G 0,75	7,1	45,0	112,0	7 G 2,5	14,0	214,3	350,0
5 G 0,75	7,8	54,0	126,0	12 G 2,5	17,3	345,8	541,0
7 G 0,75	9,2	78,0	165,0	18 G 2,5	20,9	526,1	840,0
12 G 0,75	11,4	112,0	231,0	25 G 2,5	24,3	712,4	1160,0
18 G 0,75	13,6	182,0	330,0				
25 G 0,75	16,4	250,0	459,0	4 G 4	12,6	205,0	349,0
34 G 0,75	18,6	330,0	571,0	5 G 4	13,7	237,0	423,0
42 G 0,75	21,2	415,0	706,0	7 G 4	16,1	343,0	592,0
3 G 1	7,3	45,0	109,0	4 G 6	16,0	297,0	489,0
4 G 1	8,0	58,0	126,0	7 G 6	20,4	496,0	874,0
5 G 1	8,7	68,0	147,0				
7 G 1	10,4	100,0	195,0	4 G 10	19,4	473,0	842,0
12 G 1	12,8	145,0	292,0	7 G 10	25,6	785,0	1473,0
18 G 1	15,3	235,0	418,0				
25 G 1	18,8	325,0	575,0	4 G 16	23,4	723,0	1173,0
34 G 1	21,3	455,0	716,0	7 G 16	31,1	1228,0	2050,0
42 G 1	23,9	535,0	884,0				
				4 G 25	27,3	1089,0	1510,0

注：以上电缆最小起定量1000米。